

32-010 Permissible combinations springs — shock absorbers

Combinations springs — shock absorbers

Model	Front spring	Shock absorber front (optional) Part no.	Vehicles without level control		Vehicles with level control	
	Part no.		Rear spring Part no.	Shock absorber (optional) Part no.	Rear spring Part no.	Spring strut Part no.

A. Sedans and coupes with standard suspension

123.020 123.023	123 321 27 04 ¹⁾ 123 321 37 04 123 321 39 04 ¹⁾	123 323 17 00 123 323 25 00 123 323 27 00 ¹⁰⁾	123 324 14 04 ²⁾ 123 324 06 04 ³⁾	123 326 06 00 123 326 16 00 ¹¹⁾ 123 326 18 00 ¹²⁾	123 324 15 04	123 320 04 13 ⁷⁾ 123 320 10 13 ⁸⁾			
123.026	123 321 21 04 123 321 27 04 ¹⁾								
123.030 123.033	123 321 21 04 123 321 27 04 ¹⁾ 123 321 36 04 ¹⁾								
123.043	123 324 27 04 ¹⁾ 123 321 39 04								
123.050 123.053	123 321 21 04 123 321 27 04 ¹⁾ 123 321 36 04 ¹⁾								
123.120 123.123 123.126	123 321 39 04 123 321 27 04 ¹⁾								
123.130	123 321 27 04 123 321 36 04 ¹⁾						115 324 34 04 ⁵⁾ (115 320 00 20) ⁴⁾ 123 324 35 04 ⁶⁾	115 324 37 04 (115 320 02 20) ⁴⁾ 123 324 31 04 ⁹⁾	
123.133	123 321 36 04 123 321 41 04						123 324 36 04	—	—
123.150 123.153	123 321 36 04						123 324 36 04	—	—
123.220 123.223 123.234	123 321 27 04 ¹⁾ 123 321 37 04 123 321 39 04 ¹⁾						123 324 06 04	123 324 15 04	123 320 10 13

When installing springs, pay attention to tables "Installation of springs"!

- ¹⁾ Valid for vehicles with additional special equipments (refer to adjustment of front springs).
- ²⁾ 1st version (up to February 1977).
- ³⁾ 2nd version (starting March 1977).
- ⁴⁾ Spare parts scope of delivery with rubber hose slipped on lower coil runout.
- ⁵⁾ 1st version (up to October 1978).
- ⁶⁾ 2nd version (starting November 1978).
- ⁷⁾ 1st version with 22 mm piston rod dia. (up to June 1979).
- ⁸⁾ 2nd version with 24 mm piston rod dia. (starting July 1979).
- ⁹⁾ Version without rubber hose (entering production starting 1982).
- ¹⁰⁾ Shock absorber with separating piston, replacement for 123 323 20 00.
- ¹¹⁾ Shock absorber with separating piston (replacement for 123 324 10 00).
- ¹²⁾ Shock absorber with separating piston (replacement for 123 324 15 00).

Model	Front spring	Shock absorber front (optional)	Vehicles without level control		Vehicle with level control	
	Part no.	Part no.	Rear spring Part no.	Shock absorber (optional) Part no.	Rear spring Part no.	Spring strut Part no.

Sedans, police version with standard suspension

123.020 123.023	123 321 27 04 ¹⁾ 123 321 37 04 123 321 39 04 ¹⁾	123 323 18 00 123 323 28 00	123 324 06 04	123 326 07 00 123 326 17 00	123 324 15 04	123 320 11 13
123.026	123 321 21 04 123 321 27 04 ¹⁾ 123 321 36 04 ¹⁾					
123.030 123.033	123 321 21 04 123 321 27 04 ¹⁾ 123 321 36 04 ¹⁾					
123.120 123.123 123.126	123 321 39 04 123 321 27 04 ¹⁾ 123 321 36 04 ¹⁾					
123.130	123 321 27 04 123 321 36 04 ¹⁾		123 324 35 04		115 324 37 04 (115 320 02 20) ²⁾ 123 324 31 04 ³⁾	
123.220 123.223	123 321 27 04 ¹⁾ 123 321 37 04 123 321 39 04 ¹⁾		123 324 06 04		123 324 15 04	

Model	Front spring	Shock absorber front (optional)	Vehicles with level control	
	Part no.	Part no.	Rear spring Part no.	Rear spring strut Part no.

T-sedans, police version with standard suspension

123.093	123 321 27 04 123 321 36 04	123 323 18 00 123 323 28 00	123 324 41 04	123 320 08 13
123.183	123 321 39 04 123 321 27 04 ¹⁾ 123 321 36 04 ¹⁾			
123.190	123 321 27 04 123 321 36 04 ¹⁾			
123.193	123 321 27 04 123 321 36 04 ¹⁾ 123 321 41 04 ¹⁾			
123.280 123.283	123 321 37 04 123 321 39 04 ¹⁾ 123 321 27 04 ¹⁾			

When installing springs, pay attention to tables „Adjustment of springs“!

¹⁾ Valid for vehicles with additional special equipment (refer to adjustment of front springs).

²⁾ Spare parts scope of delivery with rubber hose slipped on lower coil.

³⁾ Version without rubber hose (entering production starting 1982).

Model	Front spring	Shock absorber front (optional)	Vehicles with level control	
	Part no.	Part no.	Rear spring Part no.	Spring strut rear Part no.

C. T-sedans

Standard version with normal additional load

(permissible rear axle load 1150/1155 kg or 1195/1200 kg)

123.083	123 321 37 04 123 321 39 04 123 321 27 04 ¹⁾	123 323 17 00 123 323 25 00 123 323 27 00 ¹⁰⁾	123 324 29 04 ¹²⁾ 123 324 41 04 ¹³⁾	123 320 07 13
123.086	123 321 21 04 123 321 27 04 ¹⁾			
123.093	123 321 21 04 123 321 27 04 ¹⁾ 123 321 36 04 ¹⁾			
123.183	123 321 39 04 123 321 27 04 ¹⁾		115 324 38 04 (115 320 03 20) ⁵⁾	
123.190 123.193	123 321 27 04 123 321 36 04 ¹⁾			
123.280 123.283	123 321 37 04 123 321 39 04 ¹⁾ 123 321 27 04 ¹⁾		123 324 41 04	

Special version with higher additional load

(permissible rear axle load 1295/1300 kg)

123.083	123 321 21 04 123 321 27 04 ¹⁾	123 323 18 00 123 323 28 00 ⁹⁾	123 324 38 04 ¹¹⁾	123 320 08 13
123.086	123 321 39 04 123 321 27 04 ¹⁾ 123 321 36 04 ¹⁾			
123.183	123 321 39 04 123 321 27 04 123 321 36 04 ¹⁾			
123.190	123 321 27 04 123 321 36 04 ¹⁾			
123.193	123 321 36 04 123 321 41 04 ¹⁾			
123.280 123.283	123 321 21 04 123 321 27 04 ¹⁾ 123 321 36 04 ¹⁾			

Special version with normal additional load and harder suspension for countries with poor road conditions

(permissible rear axle load 1150/1155 kg or 1195/1200 kg)

123.083	123 321 39 04 123 321 27 04 ¹⁾	123 323 18 00 123 323 28 00 ⁹⁾	123 324 34 04 ¹²⁾ 115 324 22 04 ¹³⁾	123 320 08 13
123.086	123 321 21 04 123 321 27 04 ¹⁾ 123 321 36 04 ¹⁾			
123.093	123 321 27 04 ¹⁾ 123 321 36 04 ¹⁾			
123.183	123 321 39 04 123 321 27 04 ¹⁾ 123 321 36 04 ¹⁾		123 324 35 04 ¹²⁾ 115 324 36 04 ¹³⁾ (115 320 01 20) ⁵⁾ 123 324 33 04 ⁸⁾	
123.190	123 321 27 04 123 321 36 04 ¹⁾ 123 321 41 04 ¹⁾			
123.193	123 321 36 04 123 321 41 04 ¹⁾		123 324 22 04	
123.280 123.283	123 321 39 04 123 321 27 04 ¹⁾	123 323 18 00 123 323 28 00	123 324 22 04	