

B. Model 114, 115 standard version

Model	Front spring Part no.	Shock absorber front Designation Part no.	Rear spring Part no.	Shock absorber or strut rear Designation Part no.
-------	--------------------------	---	-------------------------	--


Standard suspension (vehicles **without** level control on rear axle)

114.010 114.011 114.015 114.02 115.010 115.015 115.017 115.110 115.115 115.117	115 321 29 04 114 321 05 04 ¹⁾ 115 321 09 04 ⁵⁾	Bilstein 115 323 10 00 F & S 115 323 13 00 ³⁾ 115 323 17 00 ³⁾ 115 323 20 00 ⁴⁾ 115 323 25 00 ⁸⁾	115 324 21 04 ²⁾ 114 324 05 04 ³⁾	Bilstein 115 326 14 00 ²⁾ 115 326 21 00 ³⁾ F & S 115 326 17 00 ²⁾ 115 326 19 00 ³⁾ 115 326 25 00 ⁴⁾ 115 326 29 00 ⁸⁾
114.06 114.07	114 321 05 04 114 321 09 04 ¹⁾ 115 321 32 04 ⁵⁾	Boge 115 323 23 00	114 324 05 04	115 326 29 00 ⁸⁾
115.114			115 324 34 04 (115 320 00 20) ⁶⁾	Boge 115 326 28 00

Standard suspension (vehicles **with** level control on rear axle)

114.010 114.011 114.015 114.02 115.010 115.015 115.017 115.110 115.115 115.117	115 321 29 04 114 321 05 04 ¹⁾	Bilstein 115 323 10 00 F & S 115 323 13 00 ²⁾ 115 323 17 00 ³⁾ 115 323 20 00 ⁴⁾ 115 323 25 00 ⁸⁾	114 324 02 04	114 320 06 13 ²⁾ 114 320 12 13 ³⁾ 123 320 10 13 ⁷⁾
114.06 114.07	114 321 05 04 114 321 09 04 ¹⁾	Boge 115 323 23 00	115 324 37 04 (115 320 02 20) ⁶⁾	
115.114				

During installation of springs, pay attention to tables "Adjustment of springs".

- 1) Valid for vehicles with additional special equipment (refer to "Adjustment of front springs").
- 2) 1st version.
- 3) 2nd version.
- 4) 3rd version.
- 5) Valid for  1974.
- 6) Spare parts scope of delivery with rubber hose slipped onto lower coil runout.
- 7) 4th version with 24 mm piston rod dia. (install in the event of repairs).
- 8) Shock absorber with separating piston.

Model	Front spring Part no.	Shock absorber front Designation Part no.	Rear spring Part no.	Shock absorber or strut rear Designation Part no.
-------	--------------------------	---	-------------------------	--

Special version: Suspension for special sedans with increased permissible rear axle load of 1160 kg,
e.g. police radio cars
(vehicles **with** level control on rear axle)

114.010 114.011 114.015 115.010 115.015 115.017 115.110 115.115 115.117	115 321 30 04 114 321 06 04 ¹⁾	Bilstein 115 323 11 00 F & S 115 323 14 00 ²⁾ 115 323 18 00 ³⁾ 115 323 21 00 ⁴⁾ 115 323 26 00 ⁶⁾	115 324 22 04	114 320 07 13 ²⁾ 114 320 14 13 ³⁾ 123 320 05 13 ⁴⁾ 123 320 11 13 ⁵⁾
114.06	114 321 06 04 114 321 07 04 ¹⁾			
115.114			115 324 36 04	

Special version: Suspension for station wagons
(vehicles **with** level control on rear axle)

114.007 115.102 115.107	115 321 30 04 114 321 06 04 ¹⁾	Bilstein 115 323 11 00 F & S 115 323 14 00 ²⁾ 115 323 18 00 ³⁾ 115 323 21 00 ⁴⁾ 115 323 26 00 ⁶⁾	115 324 29 04	114 320 07 13 ²⁾ 114 320 14 13 ³⁾ 123 320 05 13 ⁴⁾ 123 320 11 13 ⁵⁾
115.002	115 321 30 04			

Special version: Suspension for ambulance with normal wheel base 2750 mm
(vehicles **without** level control on rear axle)

114.005 115.100 115.105	115 321 30 04 114 321 06 04 ¹⁾	Bilstein 115 323 11 00 F & S 115 323 14 00 ²⁾ 115 323 18 00 ³⁾ 115 323 21 00 ⁴⁾ 115 323 26 00 ⁶⁾	115 324 29 04	Bilstein 115 326 15 00 F & S 115 326 18 00 ²⁾ 115 326 20 00 ³⁾ 115 326 26 00 ⁴⁾ 115 326 30 00 ⁶⁾
115.000 115.005	115 321 30 04			

Special version: Suspension for ambulances with normal wheel base 2750 mm
(vehicles **with** level control on rear axle)

114.005 115.100 115.105	115 321 30 04 114 321 06 04 ¹⁾	Bilstein 115 323 11 00 F & S 115 323 14 00 ²⁾ 115 323 18 00 ³⁾ 115 323 21 00 ⁴⁾ 115 323 26 00 ⁶⁾	115 324 22 04	114 320 07 13 ²⁾ 114 320 14 13 ³⁾ 123 320 05 13 ⁴⁾ 123 320 11 13 ⁵⁾
115.000 115.005	115 321 30 04			

Special version: Suspension for ambulances with longer wheel base 3400 mm
(vehicles **with** level control on rear axle)

114.008 115.103 115.108	114 321 07 04	Bilstein 115 323 11 00 F & S 115 323 14 00 ²⁾ 115 323 18 00 ³⁾ 115 323 21 00 ⁴⁾ 115 323 26 00 ⁶⁾	115 324 29 04	114 320 07 13 ²⁾ 114 320 14 13 ³⁾ 123 320 05 13 ⁴⁾ 123 320 11 13 ⁵⁾
-------------------------------	---------------	--	---------------	--

During installation of springs, pay attention to tables "Adjustment of springs".

- 1) Valid for vehicles with additional special equipment (refer to "Adjustment of front springs").
- 2) 1st version.
- 3) 2nd version.
- 4) 3rd version.
- 5) 4th version with 24 mm piston rod dia. (install in the event of repairs).
- 6) Shock absorber with separating piston.