

B. Models 114, 115 standard version

Adjustment of front springs (association front springs -- rubber mounts)

Model	Front spring Part no.	Height of spring rubber mounts according to vehicle equipment (slide roof, power steering, automatic transmission, air-conditioning) and color code of spring									
		Special equipment									
		None		1		2		3 or air conditioning system		1-3 and air conditioning system	
		Color code of spring									
		blue	red	blue	red	blue	red	blue	red	blue	red

Standard suspension

114.010 114.011 114.021 114.023 115.115	115 321 29 04	18	23	—	—	—	—	—	—	—	—
	114 321 05 04	—	—	8	13	13	18	13	18	23	—
114.015	115 321 29 04	13	18	18	23	—	—	—	—	—	—
	114 321 05 04	—	—	—	—	8	13	13	18	18	23
114.022 115.110 115.117	115 321 29 04	18	23	—	—	—	—	—	—	—	—
	114 321 05 04	—	—	8	13	13	18	18	23	23	—
114.060 ¹⁾ 114.073	114 321 05 04	13	18	13	18	18	23	—	—	—	—
	114 321 09 04	—	—	—	—	—	—	8	13	13	18
114.062 ¹⁾ 114.072	114 321 05 04	13	18	18	23	18	23	—	—	—	—
	114 321 09 04	—	—	—	—	—	—	8	13	13	18
115.010 115.015 115.017	115 321 29 04	13	18	13	18	18	23	18	23	—	—
	114 321 05 04	—	—	—	—	—	—	—	—	13	18
115.114	114 321 05 04	18	23	18	23	—	—	—	—	—	—
	114 321 09 04	—	—	—	—	8	13	13	18	18	23

¹⁾ On righthand drive vehicles install a rubber mount on righthand side of vehicle higher by 5 mm than indicated in table.

Adjustment of front springs (association front springs – rubber mounts)

Model	Front spring Part no.	Height of spring rubber mounts according to vehicle equipment (slide roof, power steering, automatic transmission, air-conditioning and color code of spring)									
		Special equipment									
		None		1		2		3 or air conditioning system		1–3 and air conditioning system	
		Color code of spring		Color code of spring		Color code of spring		Color code of spring		Color code of spring	
		blue	red	blue	red	blue	red	blue	red	blue	red

Special version: Harder suspension for poor road conditions

114.010 114.011 114.021 114.023 115.115	115 321 30 04	13	18	18	23	18	23	–	–	–	–
	114 321 06 04	–	–	–	–	–	–	8	13	13	18
114.015	115 321 30 04	13	18	13	18	18	23	18	23	–	–
	114 321 06 04	–	–	–	–	–	–	–	–	8	13
114.022 115.110 115.117	115 321 30 04	13	18	18	23	–	–	–	–	–	–
	114 321 06 04	–	–	–	–	8	13	8	13	13	18
114.060 ¹⁾ 114.073	114 321 06 04	8	13	8	13	13	18	13	18	–	–
	114 321 07 04	–	–	–	–	–	–	–	–	8	13
114.062 ¹⁾ 114.072	114 321 06 04	8	13	8	13	13	18	18	23	–	–
	114 321 07 04	–	–	–	–	–	–	–	–	8	13
115.010 115.015 115.017	115 321 30 04	8	13	8	13	13	18	13	18	–	–
	114 321 06 04	–	–	–	–	–	–	–	–	8	13
115.114	114 321 06 04	13	18	13	18	18	23	–	–	–	–
	114 321 07 04	–	–	–	–	–	–	8	13	13	18

Special version: Suspension for special sedans with higher permissible rear axle load of 1160 kg, e.g. police radio cars

114.010 114.011 114.015 115.110 115.115 115.117	115 321 30 04	13	18	13	18	18	23	18	23	–	–
	114 321 06 04	–	–	–	–	8	13	8	13	–	–
114.06	114 321 06 04	13	18	18	23	18	23	18	23	–	–
115.010 115.015 115.017	115 321 30 04	8	13	8	13	13	18	13	18	–	–
115.114	114 321 06 04	13	18	13	18	18	23	18	23	–	–
	114 321 07 04	–	–	–	–	–	–	8	13	–	–

¹⁾ On righthand drive vehicles install a rubber mount on righthand side of vehicle higher by 5 mm than indicated in table.

Adjustment of front springs (association front springs – rubber mounts)

Model	Front spring Part no.	Height of spring rubber mounts according to vehicle equipment (slide roof, power steering, automatic transmission, air-conditioning) and color code of spring									
		Special equipment									
		None		1		2		3 or air conditioning system		1-3 and air condition-system	
Color code of spring											
blue		red		blue		red		blue		red	

Special version: Springs for special sedans with longer wheel base 3400 mm

114.017	114 321 06 04	18	23	–	–	–	–	–	–	–	–
	114 321 07 04	–	–	8	13	8	13	13	18	18	23
115.112 115.119	114 321 07 04	8	13	8	13	13	18	18	23	23	–

Special version: Suspension for special sedans with longer wheel base 3400 mm

114.005 114.007	115 321 30 04	13	18	13	18	18	23	18	23	–	–
115.100 115.105	115 321 30 04	18	23	18	23	–	–	–	–	–	–
	114 321 06 04	–	–	–	–	8	13	–	–	–	–
115.102 115.107	115 321 30 04	13	18	18	23	–	–	–	–	–	–
	114 321 06 04	–	–	–	–	8	13	8	13	–	–
115.000 115.005	115 321 30 04	8	13	13	18	13	18	–	–	–	–
115.002	115 321 30 04	8	13	8	13	13	18	13	18	–	–

Special version: Springs for ambulances with longer wheel base 3400 mm

114.008	114 321 07 04	8	13	8	13	13	18	–	–	–	–
115.103 115.108	114 321 07 04	8	13	13	18	13	18	–	–	–	–