What You Should Know at the Gas Station

- **Fuel:**

  Use premium unleaded gasoline: Posted Octane 91 (Average of 96 RON/86 MON).

  Fuel tank capacity approx. 90 l (23.8 US gal). This includes approx. 12.5 l (3.3 US gal) reserve.

  Only fill fuel tank until the filler nozzle unit cuts out – do not overfill.

> **Warning!**
>
> **Gasoline vapor is highly flammable. It burns violently and can cause serious injury. Whenever you are around gasoline, extinquish all smoking materials. Never get sparks, flame or smoking materials near gasoline!**

- **Engine Oil:**

  Engine oil level check, see page 77.

  Quantity differential between upper and lower dipstick marking level: 2.0 l (2.1 US qt).

  Recommended engine oils see page 111.

- **Automatic Transmission:**

  MB Automatic transmission fluid.

  For level checks and replenishment, refer to page 78.

- **Coolant:**

  For normal replenishing, use water (potable water quality).

  For further information (e.g. anticorrosion/ antifreeze), refer to page 116.

- **Spark Plugs:**

  Approved spark plugs, refer to "Technical Data".

- **Bulbs:**

  High and low beams: Halogen type 9004,
  fog lamps: Halogen type H 3,
  tail, parking and standing lamps 10 W/6 cp,
  turn signal, standing, side marker and parking lamps, front 21/5 W/32/3 cp,
  turn signal lamps, rear 21 W/32 cp,
  stop lamps 21 W/32 cp,
  license plate lamps 5 W.

- **Tire Pressure:**

  For tire pressure, refer to tire pressure chart inside the fuel filler flap.